

Declaration of Conformity – Ref.No 44001

In compliance with the Construction Products Regulation and The Construction Products (Amendment etc.) (EU Exit) Regulations 2020.

1. Identification code of product-type	High-pressure decorative compact laminate CGF-LK																																																					
2. Identification	CGF-LK: Duropal HPL Compact Pyroex, black core																																																					
3. Intended use	Compact laminate intended for internal wall and ceiling finishes (including suspended ceilings)																																																					
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D – 88299 Leutkirch																																																					
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt																																																					
6. System of assessment and verification	System 1																																																					
7. Assessment of performance	The notified body BTTG® (Approved Body No. 0338) issued the certificate of constancy of conformity 0338-CPR-5591 of the conformity of the construction product under system 1 based on: determination of the product-type, initial inspection of the manufacturing plant and of factory production control. The Approved Body No. 0338 performs the continuous surveillance, assessment and evaluation of factory production control.																																																					
8. European Technical Assessment	not relevant																																																					
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>CGF-LK</th> <th>CGF-LK</th> </tr> </thead> <tbody> <tr> <td>Thickness</td> <td>4–5 mm</td> <td>6 mm</td> </tr> <tr> <td><i>Essential characteristics/main features</i></td> <td colspan="2"><i>Declared performance</i></td> </tr> <tr> <td>Reaction to fire (Euroclass)</td> <td colspan="2">C-s2,d0</td> </tr> <tr> <td>Fire resistance</td> <td colspan="2">NPD</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td colspan="2">110</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td colspan="2">250</td> </tr> <tr> <td>Resistance to fixings (face)</td> <td>min. 1,000 N</td> <td>min. 2,000 N</td> </tr> <tr> <td>Resistance to fixings (edge)</td> <td colspan="2">NPD</td> </tr> <tr> <td>Direct airborne sound insulation</td> <td colspan="2">NPD</td> </tr> <tr> <td>Flexural strength</td> <td colspan="2">min. 80 MPa</td> </tr> <tr> <td>Bending modulus of elasticity</td> <td colspan="2">min. 9,000 MPa</td> </tr> <tr> <td>Thermal conductivity</td> <td colspan="2">approx. 0.3 W/(mK)</td> </tr> <tr> <td>Formaldehyde release</td> <td colspan="2">E1 E05</td> </tr> <tr> <td>Sound absorption</td> <td colspan="2">NPD</td> </tr> <tr> <td>Durability – Resistance to immersion in boiling water</td> <td colspan="2">passed</td> </tr> <tr> <td>Density</td> <td colspan="2">min. 1,350 kg/m³</td> </tr> </tbody> </table>		Identification code	CGF-LK	CGF-LK	Thickness	4–5 mm	6 mm	<i>Essential characteristics/main features</i>	<i>Declared performance</i>		Reaction to fire (Euroclass)	C-s2,d0		Fire resistance	NPD		Water vapour permeability (wet cup)	110		Water vapour permeability (dry cup)	250		Resistance to fixings (face)	min. 1,000 N	min. 2,000 N	Resistance to fixings (edge)	NPD		Direct airborne sound insulation	NPD		Flexural strength	min. 80 MPa		Bending modulus of elasticity	min. 9,000 MPa		Thermal conductivity	approx. 0.3 W/(mK)		Formaldehyde release	E1 E05		Sound absorption	NPD		Durability – Resistance to immersion in boiling water	passed		Density	min. 1,350 kg/m ³		<i>Harmonised technical specification</i> EN 438-7:2005
Identification code	CGF-LK	CGF-LK																																																				
Thickness	4–5 mm	6 mm																																																				
<i>Essential characteristics/main features</i>	<i>Declared performance</i>																																																					
Reaction to fire (Euroclass)	C-s2,d0																																																					
Fire resistance	NPD																																																					
Water vapour permeability (wet cup)	110																																																					
Water vapour permeability (dry cup)	250																																																					
Resistance to fixings (face)	min. 1,000 N	min. 2,000 N																																																				
Resistance to fixings (edge)	NPD																																																					
Direct airborne sound insulation	NPD																																																					
Flexural strength	min. 80 MPa																																																					
Bending modulus of elasticity	min. 9,000 MPa																																																					
Thermal conductivity	approx. 0.3 W/(mK)																																																					
Formaldehyde release	E1 E05																																																					
Sound absorption	NPD																																																					
Durability – Resistance to immersion in boiling water	passed																																																					
Density	min. 1,350 kg/m ³																																																					
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This Declaration of Conformity is issued under the sole responsibility of the manufacturer identified in point 4.																																																						

Signed for and on behalf of the manufacturer by:

Date of issue: 2023-04-05

Diethard Singer
 General Manager / Pfleiderer Leutkirch GmbH
 (Document was created electronically and is therefore valid without signature!)

NPD: performance not defined