

Declaration of Performance (CE) – Ref.No 030

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	Lacquered, decorative particleboard PB100-LK														
2. Identification	PB100-LK: PrimeBoard XTreme P2 / PrimeBoard XTreme P2 CARB2														
3. Intended use	Boards for interior fitments (including furniture) for use in dry conditions														
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D – 88299 Leutkirch														
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt														
6. System of assessment and verification	System 4														
7. Assessment of performance	not relevant														
8. European Technical Assessment	not relevant														
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>PB100-LK</th> <th>PB100-LK</th> <th>PB100-LK</th> <th>PB100-LK</th> </tr> </thead> <tbody> <tr> <td>Thickness</td> <td>10–13 mm</td> <td>16–19 mm</td> <td>22–25 mm</td> <td>28 mm</td> </tr> </tbody> </table>				Identification code	PB100-LK	PB100-LK	PB100-LK	PB100-LK	Thickness	10–13 mm	16–19 mm	22–25 mm	28 mm	<i>Harmonised technical specification</i> EN 13986:2004 +A1:2015
Identification code	PB100-LK	PB100-LK	PB100-LK	PB100-LK											
Thickness	10–13 mm	16–19 mm	22–25 mm	28 mm											
<i>Essential characteristics/main features</i>	<i>Declared performance</i>														
Reaction to fire (Euroclass)	D-s2,d0 according to EN 13986 dependent on end use (Thickness: ≥ 9 mm / Gross density: ≥ 600 kg/m ³)														
Water vapour permeability (wet cup)	15														
Water vapour permeability (dry cup)	50														
Formaldehyde release	E1 E05														
content of pentachlorophenol	≤ 3 ppm														
Airborne sound insulation (surface mass)	NPD														
Sound Absorption frequency range 250 Hz to 500 Hz	0.1														
Sound Absorption frequency range 1000 Hz to 2000 Hz	0.25														
Thermal conductivity	approx. 0.12 W/(mK)														
Air permeability	NPD														
Internal bond	0.4 N/mm ²	0.35 N/mm ²	0.3 N/mm ²	0.25 N/mm ²											
Swelling in thickness, 24 h	NPD														
Internal bond after boil test	NPD														
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.															

Signed for and on behalf of the manufacturer by:

Date of issue: 2024-03-18

Diethard Singer
 General Manager / Pfleiderer Leutkirch GmbH
 (Document was created electronically and is therefore valid without signature!)

NPD: performance not defined
 Technical values refer to the core material