

Declaration of Performance - Ref.No 018

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	HPL composite panel VE1210-LK																																																													
2. Identification	VE1210-LK: Duropal Element MDF plus																																																													
3. Intended use	HPL composite panel intended for internal wall and ceiling finishes (including suspended ceilings)																																																													
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D-88299 Leutkirch																																																													
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D-92318 Neumarkt																																																													
6. System of assessment and verification	System 4																																																													
7. Assessment of performance	not relevant																																																													
8. European Technical Assessment	not relevant																																																													
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>VE1210-LK</th> <th>VE1210-LK</th> <th rowspan="2"><i>Harmonised technical specification</i></th> </tr> <tr> <th>Thickness</th> <td>9.6 mm</td> <td>17.6–20.6 mm</td> </tr> <tr> <th><i>Essential characteristics/main features</i></th> <th colspan="2"><i>Declared performance</i></th> <th rowspan="16">EN 438-7:2005</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire (Euroclass)</td> <td>NPD</td> <td>D-s2,d0</td> </tr> <tr> <td>Fire resistance</td> <td colspan="2">NPD</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td colspan="2">12</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td colspan="2">20</td> </tr> <tr> <td>Resistance to fixings (face)</td> <td>min. 70 N/mm</td> <td>min. 1,200 N</td> </tr> <tr> <td>Resistance to fixings (edge)</td> <td>NPD</td> <td>min. 800 N</td> </tr> <tr> <td>Direct airborne sound insulation</td> <td colspan="2">NPD</td> </tr> <tr> <td>Bonding strength</td> <td colspan="2">min. 0.8 N/mm²</td> </tr> <tr> <td>Flexural tensile strength</td> <td colspan="2">min. 0.8 N/mm²</td> </tr> <tr> <td>Thermal conductivity</td> <td colspan="2">approx. 0.14 W/(mK)</td> </tr> <tr> <td>content of pentachlorophenol</td> <td colspan="2">max. 3 ppm</td> </tr> <tr> <td>Formaldehyde release</td> <td colspan="2">E1 E05 CARB Phase 2 / TSCA Title VI</td> </tr> <tr> <td>Sound absorption</td> <td colspan="2">NPD</td> </tr> <tr> <td>Durability - Glue-line quality</td> <td colspan="2">min. 3 rating</td> </tr> <tr> <td>Durability - Resistance to elevated temperature</td> <td colspan="2">no effect</td> </tr> <tr> <td>Durability - Water resistance</td> <td colspan="2">max. 20 %</td> </tr> </tbody> </table>			Identification code	VE1210-LK	VE1210-LK	<i>Harmonised technical specification</i>	Thickness	9.6 mm	17.6–20.6 mm	<i>Essential characteristics/main features</i>	<i>Declared performance</i>		EN 438-7:2005	Reaction to fire (Euroclass)	NPD	D-s2,d0	Fire resistance	NPD		Water vapour permeability (wet cup)	12		Water vapour permeability (dry cup)	20		Resistance to fixings (face)	min. 70 N/mm	min. 1,200 N	Resistance to fixings (edge)	NPD	min. 800 N	Direct airborne sound insulation	NPD		Bonding strength	min. 0.8 N/mm ²		Flexural tensile strength	min. 0.8 N/mm ²		Thermal conductivity	approx. 0.14 W/(mK)		content of pentachlorophenol	max. 3 ppm		Formaldehyde release	E1 E05 CARB Phase 2 / TSCA Title VI		Sound absorption	NPD		Durability - Glue-line quality	min. 3 rating		Durability - Resistance to elevated temperature	no effect		Durability - Water resistance	max. 20 %	
Identification code	VE1210-LK	VE1210-LK	<i>Harmonised technical specification</i>																																																											
Thickness	9.6 mm	17.6–20.6 mm																																																												
<i>Essential characteristics/main features</i>	<i>Declared performance</i>		EN 438-7:2005																																																											
Reaction to fire (Euroclass)	NPD	D-s2,d0																																																												
Fire resistance	NPD																																																													
Water vapour permeability (wet cup)	12																																																													
Water vapour permeability (dry cup)	20																																																													
Resistance to fixings (face)	min. 70 N/mm	min. 1,200 N																																																												
Resistance to fixings (edge)	NPD	min. 800 N																																																												
Direct airborne sound insulation	NPD																																																													
Bonding strength	min. 0.8 N/mm ²																																																													
Flexural tensile strength	min. 0.8 N/mm ²																																																													
Thermal conductivity	approx. 0.14 W/(mK)																																																													
content of pentachlorophenol	max. 3 ppm																																																													
Formaldehyde release	E1 E05 CARB Phase 2 / TSCA Title VI																																																													
Sound absorption	NPD																																																													
Durability - Glue-line quality	min. 3 rating																																																													
Durability - Resistance to elevated temperature	no effect																																																													
Durability - Water resistance	max. 20 %																																																													
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.																																																														
Signed for and on behalf of the manufacturer by:																																																														
Date of issue: 2021-02-02	Diethard Singer General Manager / Pfleiderer Leutkirch GmbH (Document was created electronically and is therefore valid without signature!)																																																													

NPD: performance not defined