

Declaration of Performance (CE) – Ref.No 001

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	High-pressure decorative compact laminate CGF-LK																																																																																										
2. Identification	CGF-LK: Duropal HPL Compact Pyroex, black core																																																																																										
3. Intended use	Compact laminate intended for internal wall and ceiling finishes (including suspended ceilings)																																																																																										
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D – 88299 Leutkirch																																																																																										
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt																																																																																										
6. System of assessment and verification	System 1																																																																																										
7. Assessment of performance	The notified body Fraunhofer-Institut für Holzforschung WKI Braunschweig (NB No. 0765) issued the certificate of constancy of performance 0765-CPR-1399 of the conformity of the construction product under system 1 based on: determination of the product-type, initial inspection of the manufacturing plant and of factory production control. The NB no. 0765 performs the continuous surveillance, assessment and evaluation of factory production control.																																																																																										
8. European Technical Assessment	not relevant																																																																																										
9. Declared performance	<table><tr><td>Identification code</td><td>CGF-LK</td><td>CGF-LK</td><td>CGF-LK</td><td>CGF-LK</td><td rowspan="18">Harmonised technical specification EN 438-7:2005</td></tr><tr><td>Thickness</td><td>4–5 mm</td><td>6 mm</td><td>8 mm</td><td>10–15 mm</td></tr><tr><td>Essential characteristics/main features</td><td colspan="4">Declared performance</td></tr><tr><td>Reaction to fire (Euroclass)</td><td colspan="2">C-s2,d0</td><td colspan="2">B-s1,d0</td></tr><tr><td>Fire resistance</td><td colspan="4">NPD</td></tr><tr><td>Water vapour permeability (wet cup)</td><td colspan="4">110</td></tr><tr><td>Water vapour permeability (dry cup)</td><td colspan="4">250</td></tr><tr><td>Resistance to fixings (face)</td><td>min. 1,000 N</td><td>min. 2,000 N</td><td>min. 3,000 N</td><td>min. 4,000 N</td></tr><tr><td>Resistance to fixings (edge)</td><td colspan="4">NPD</td></tr><tr><td>Direct airborne sound insulation</td><td colspan="4">NPD</td></tr><tr><td>Flexural strength</td><td colspan="4">min. 80 MPa</td></tr><tr><td>Bending modulus of elasticity</td><td colspan="4">min. 9,000 MPa</td></tr><tr><td>Thermal conductivity</td><td colspan="4">approx. 0.3 W/(mK)</td></tr><tr><td>Formaldehyde release</td><td colspan="4">E1 E05</td></tr><tr><td>Sound absorption</td><td colspan="4">NPD</td></tr><tr><td>Durability – Resistance to immersion in boiling water</td><td colspan="4">passed</td></tr><tr><td>Density</td><td colspan="4">min. 1,350 kg/m³</td></tr></table>					Identification code	CGF-LK	CGF-LK	CGF-LK	CGF-LK	Harmonised technical specification EN 438-7:2005	Thickness	4–5 mm	6 mm	8 mm	10–15 mm	Essential characteristics/main features	Declared performance				Reaction to fire (Euroclass)	C-s2,d0		B-s1,d0		Fire resistance	NPD				Water vapour permeability (wet cup)	110				Water vapour permeability (dry cup)	250				Resistance to fixings (face)	min. 1,000 N	min. 2,000 N	min. 3,000 N	min. 4,000 N	Resistance to fixings (edge)	NPD				Direct airborne sound insulation	NPD				Flexural strength	min. 80 MPa				Bending modulus of elasticity	min. 9,000 MPa				Thermal conductivity	approx. 0.3 W/(mK)				Formaldehyde release	E1 E05				Sound absorption	NPD				Durability – Resistance to immersion in boiling water	passed				Density	min. 1,350 kg/m³			
Identification code	CGF-LK	CGF-LK	CGF-LK	CGF-LK	Harmonised technical specification EN 438-7:2005																																																																																						
Thickness	4–5 mm	6 mm	8 mm	10–15 mm																																																																																							
Essential characteristics/main features	Declared performance																																																																																										
Reaction to fire (Euroclass)	C-s2,d0		B-s1,d0																																																																																								
Fire resistance	NPD																																																																																										
Water vapour permeability (wet cup)	110																																																																																										
Water vapour permeability (dry cup)	250																																																																																										
Resistance to fixings (face)	min. 1,000 N	min. 2,000 N	min. 3,000 N	min. 4,000 N																																																																																							
Resistance to fixings (edge)	NPD																																																																																										
Direct airborne sound insulation	NPD																																																																																										
Flexural strength	min. 80 MPa																																																																																										
Bending modulus of elasticity	min. 9,000 MPa																																																																																										
Thermal conductivity	approx. 0.3 W/(mK)																																																																																										
Formaldehyde release	E1 E05																																																																																										
Sound absorption	NPD																																																																																										
Durability – Resistance to immersion in boiling water	passed																																																																																										
Density	min. 1,350 kg/m³																																																																																										
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.																																																																																											
Signed for and on behalf of the manufacturer by:																																																																																											
Date of issue: 2025-08-12	Dr. Björn König General Manager / Pfleiderer Leutkirch GmbH (Document was created electronically and is therefore valid without signature!)																																																																																										

NPD: performance not defined