

## Declaration of Performance (CE) – Ref.No 001

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	High-pressure decorative compact laminate CGF-LK																																																																																																											
2. Identification	CGF-LK: Duropal HPL Compact Pyroex, black core																																																																																																											
3. Intended use	Compact laminate intended for internal wall and ceiling finishes (including suspended ceilings)																																																																																																											
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D – 88299 Leutkirch																																																																																																											
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt																																																																																																											
6. System of assessment and verification	System 1																																																																																																											
7. Assessment of performance	The notified body Fraunhofer-Institut für Holzforschung WKI Braunschweig (NB No. 0765) issued the certificate of constancy of performance 0765-CPR-1399 of the conformity of the construction product under system 1 based on: determination of the product-type, initial inspection of the manufacturing plant and of factory production control. The NB no. 0765 performs the continuous surveillance, assessment and evaluation of factory production control.																																																																																																											
8. European Technical Assessment	not relevant																																																																																																											
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>CGF-LK</th> <th>CGF-LK</th> <th>CGF-LK</th> <th>CGF-LK</th> <th>CGF-LK</th> </tr> </thead> <tbody> <tr> <td>Thickness</td> <td>4 mm</td> <td>5 mm</td> <td>6 mm</td> <td>8 mm</td> <td>10–20 mm</td> </tr> <tr> <td><i>Essential characteristics/main features</i></td> <td colspan="5"><i>Declared performance</i></td> </tr> <tr> <td>Reaction to fire (Euroclass)</td> <td>C-s2,d0</td> <td>B-s1,d0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Fire resistance</td> <td colspan="5">NPD</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td colspan="5">110</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td colspan="5">250</td> </tr> <tr> <td>Resistance to fixings (face)</td> <td colspan="2">min. 1,000 N</td> <td>min. 2,000 N</td> <td>min. 3,000 N</td> <td>min. 4,000 N</td> </tr> <tr> <td>Resistance to fixings (edge)</td> <td colspan="5">NPD</td> </tr> <tr> <td>Direct airborne sound insulation</td> <td colspan="5">NPD</td> </tr> <tr> <td>Flexural strength</td> <td colspan="5">min. 80 MPa</td> </tr> <tr> <td>Bending modulus of elasticity</td> <td colspan="5">min. 9,000 MPa</td> </tr> <tr> <td>Thermal conductivity</td> <td colspan="5">approx. 0.3 W/(mK)</td> </tr> <tr> <td>Formaldehyde release</td> <td colspan="5">E1 E05</td> </tr> <tr> <td>Sound absorption</td> <td colspan="5">NPD</td> </tr> <tr> <td>Durability – Resistance to immersion in boiling water</td> <td colspan="5">passed</td> </tr> <tr> <td>Density</td> <td colspan="5">min. 1,350 kg/m<sup>3</sup></td> </tr> </tbody> </table>					Identification code	CGF-LK	CGF-LK	CGF-LK	CGF-LK	CGF-LK	Thickness	4 mm	5 mm	6 mm	8 mm	10–20 mm	<i>Essential characteristics/main features</i>	<i>Declared performance</i>					Reaction to fire (Euroclass)	C-s2,d0	B-s1,d0				Fire resistance	NPD					Water vapour permeability (wet cup)	110					Water vapour permeability (dry cup)	250					Resistance to fixings (face)	min. 1,000 N		min. 2,000 N	min. 3,000 N	min. 4,000 N	Resistance to fixings (edge)	NPD					Direct airborne sound insulation	NPD					Flexural strength	min. 80 MPa					Bending modulus of elasticity	min. 9,000 MPa					Thermal conductivity	approx. 0.3 W/(mK)					Formaldehyde release	E1 E05					Sound absorption	NPD					Durability – Resistance to immersion in boiling water	passed					Density	min. 1,350 kg/m <sup>3</sup>					<i>Harmonised technical specification</i> EN 438-7:2005
Identification code	CGF-LK	CGF-LK	CGF-LK	CGF-LK	CGF-LK																																																																																																							
Thickness	4 mm	5 mm	6 mm	8 mm	10–20 mm																																																																																																							
<i>Essential characteristics/main features</i>	<i>Declared performance</i>																																																																																																											
Reaction to fire (Euroclass)	C-s2,d0	B-s1,d0																																																																																																										
Fire resistance	NPD																																																																																																											
Water vapour permeability (wet cup)	110																																																																																																											
Water vapour permeability (dry cup)	250																																																																																																											
Resistance to fixings (face)	min. 1,000 N		min. 2,000 N	min. 3,000 N	min. 4,000 N																																																																																																							
Resistance to fixings (edge)	NPD																																																																																																											
Direct airborne sound insulation	NPD																																																																																																											
Flexural strength	min. 80 MPa																																																																																																											
Bending modulus of elasticity	min. 9,000 MPa																																																																																																											
Thermal conductivity	approx. 0.3 W/(mK)																																																																																																											
Formaldehyde release	E1 E05																																																																																																											
Sound absorption	NPD																																																																																																											
Durability – Resistance to immersion in boiling water	passed																																																																																																											
Density	min. 1,350 kg/m <sup>3</sup>																																																																																																											
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.																																																																																																												
Signed for and on behalf of the manufacturer by:																																																																																																												
Date of issue: 2026-05-22	Dr. Björn König General Manager / Pfleiderer Leutkirch GmbH (Document was created electronically and is therefore valid without signature!)																																																																																																											

NPD: performance not defined