



Declaration of Performance (CE) - Ref.No 030

acc. to REGULATION (EU) No 305/2011 Article 4

1.	Identification code of product-type	Lacquered, decorative particleboard PB100-LK					
2.	Identification	PB100-LK: PrimeBoard XTreme High Gloss P2 / PrimeBoard XTreme SuperMatt P2					
3.	Intended use	Boards for interior fitments (including furniture) for use in dry conditions					
4.	Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D – 88299 Leutkirch					
5.	Authorised representative Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt						
6.	System of assessment and verification	em of assessment and System 4 cation					
7.	Assessment of performance	nce not relevant					
8.	European Technical Assessment	not relevant					
9. Declared performance							
	Identification code	PB100-LK	PB100-LK	PB100-LK	PB100-LK		
	Thickness	10–13 mm	16–19 mm	22–25 mm	28 mm	Harmonised technical	
Essential characteristics/main features		Declared performance				specification	
Reaction to fire (Euroclass)		D-s2,d0 NPD				EN 13986:2004 +A1:2015	
Water vapour permeability (wet cup)		15					
Water vapour permeability (dry cup)		50					
Fc	rmaldehyde release	E1 E05					
CO	ntent of pentachlorophenol	≤ 3 ppm					

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

0.35 N/mm²

Signed for and on behalf of the manufacturer by:

Date of issue: 2025-08-01

Airborne sound insulation (surface

Sound Absorption frequency range

Sound Absorption frequency range

mass)

250 Hz to 500 Hz

Air permeability

Internal bond

1000 Hz to 2000 Hz Thermal conductivity

Swelling in thickness, 24 h

Internal bond after boil test

Dr. Björn König

NPD

0.1

0.25

NPD

NPD

NPD

0.4 N/mm²

approx. 0.12 W/(mK)

General Manager / Pfleiderer Leutkirch GmbH (Document was created electronically and is therefore valid without signature!)

0.3 N/mm²

0.25 N/mm²

NPD: performance not defined Technical values refer to the core material