

## Declaration of Performance (CE) – Ref.No 053

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	HPL composite panel VE101-AR																																																																														
2. Identification	VE101-AR: Duropal Element P2 / Duropal Element microPLUS® P2 / Duropal Element XTreme P2 / Duropal Element XTreme Touch P2 / Duropal Element XTreme plus P2 / Duropal Element SolidColor P2 / Duropal Element SolidColor XTreme P2																																																																														
3. Intended use	HPL composite panel intended for internal wall and ceiling finishes (including suspended ceilings)																																																																														
4. Manufacturer	Pfleiderer Arnsberg GmbH, Westring 19 – 21, D – 59759 Arnsberg																																																																														
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt																																																																														
6. System of assessment and verification	System 4																																																																														
7. Assessment of performance	not relevant																																																																														
8. European Technical Assessment	not relevant																																																																														
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>VE101-AR</th> <th>VE101-AR</th> <th>VE101-AR</th> </tr> </thead> <tbody> <tr> <td>Thickness</td> <td>9.6–10.4 mm</td> <td>16–25.8 mm</td> <td>29.6–40.4 mm</td> </tr> <tr> <td><i>Essential characteristics/main features</i></td> <td colspan="3"><i>Declared performance</i></td> </tr> <tr> <td>Reaction to fire (Euroclass)</td> <td>NPD</td> <td>D-s2,d0</td> <td>NPD</td> </tr> <tr> <td>Fire resistance</td> <td colspan="3">NPD</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td colspan="3">15</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td colspan="3">50</td> </tr> <tr> <td>Resistance to fixings (face)</td> <td>≥ 40 N/mm</td> <td>≥ 600 N</td> <td></td> </tr> <tr> <td>Resistance to fixings (edge)</td> <td>NPD</td> <td>≥ 350 N</td> <td></td> </tr> <tr> <td>Direct airborne sound insulation</td> <td colspan="3">NPD</td> </tr> <tr> <td>Bonding strength</td> <td colspan="3">≥ 0.6 N/mm<sup>2</sup></td> </tr> <tr> <td>Flexural tensile strength</td> <td colspan="3">≥ 0.6 N/mm<sup>2</sup></td> </tr> <tr> <td>Thermal conductivity</td> <td colspan="3">approx. 0.14 W/(mK)</td> </tr> <tr> <td>content of pentachlorophenol</td> <td colspan="3">≤ 3 ppm</td> </tr> <tr> <td>Formaldehyde release</td> <td colspan="3">E1 E05</td> </tr> <tr> <td>Sound absorption</td> <td colspan="3">NPD</td> </tr> <tr> <td>Durability – Glue-line quality</td> <td colspan="3">≥ 3 rating</td> </tr> <tr> <td>Durability – Resistance to elevated temperature</td> <td colspan="3">no effect</td> </tr> <tr> <td>Durability – Water resistance</td> <td colspan="3">≤ 30 %</td> </tr> </tbody> </table>			Identification code	VE101-AR	VE101-AR	VE101-AR	Thickness	9.6–10.4 mm	16–25.8 mm	29.6–40.4 mm	<i>Essential characteristics/main features</i>	<i>Declared performance</i>			Reaction to fire (Euroclass)	NPD	D-s2,d0	NPD	Fire resistance	NPD			Water vapour permeability (wet cup)	15			Water vapour permeability (dry cup)	50			Resistance to fixings (face)	≥ 40 N/mm	≥ 600 N		Resistance to fixings (edge)	NPD	≥ 350 N		Direct airborne sound insulation	NPD			Bonding strength	≥ 0.6 N/mm <sup>2</sup>			Flexural tensile strength	≥ 0.6 N/mm <sup>2</sup>			Thermal conductivity	approx. 0.14 W/(mK)			content of pentachlorophenol	≤ 3 ppm			Formaldehyde release	E1 E05			Sound absorption	NPD			Durability – Glue-line quality	≥ 3 rating			Durability – Resistance to elevated temperature	no effect			Durability – Water resistance	≤ 30 %		
Identification code	VE101-AR	VE101-AR	VE101-AR																																																																												
Thickness	9.6–10.4 mm	16–25.8 mm	29.6–40.4 mm																																																																												
<i>Essential characteristics/main features</i>	<i>Declared performance</i>																																																																														
Reaction to fire (Euroclass)	NPD	D-s2,d0	NPD																																																																												
Fire resistance	NPD																																																																														
Water vapour permeability (wet cup)	15																																																																														
Water vapour permeability (dry cup)	50																																																																														
Resistance to fixings (face)	≥ 40 N/mm	≥ 600 N																																																																													
Resistance to fixings (edge)	NPD	≥ 350 N																																																																													
Direct airborne sound insulation	NPD																																																																														
Bonding strength	≥ 0.6 N/mm <sup>2</sup>																																																																														
Flexural tensile strength	≥ 0.6 N/mm <sup>2</sup>																																																																														
Thermal conductivity	approx. 0.14 W/(mK)																																																																														
content of pentachlorophenol	≤ 3 ppm																																																																														
Formaldehyde release	E1 E05																																																																														
Sound absorption	NPD																																																																														
Durability – Glue-line quality	≥ 3 rating																																																																														
Durability – Resistance to elevated temperature	no effect																																																																														
Durability – Water resistance	≤ 30 %																																																																														
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.	<p style="text-align: right;"><i>Harmonised technical specification</i></p> <p>EN 438-7:2005</p>																																																																														

Signed for and on behalf of the manufacturer by:

Date of issue: 2024-01-26

Dr. Björn König  
General Manager / Pfleiderer Arnsberg GmbH  
(Document was created electronically and is therefore valid without signature!)

NPD: performance not defined