



Declaration of Performance (CE) – Ref.No 2100 acc. to REGULATION (EU) No 305/2011 Article 4 1. Identification code of ClassicBoard P2, DecoBoard P2, DecoBoard Individual Motiv P2, DecoBoard P2 microPLUS® - 2100 product-type Intended use Boards for interior fitments (including furniture) for use in dry conditions Manufacturer Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt 4. Authorised representative not relevant System of assessment and System 4 vérification Assessment of performance not relevant European Technical not relevant



	Thickness	≤ 8.9 mm	> 8.9 mm to ≤ 13 mm		> 20 mm to ≤ 25 mm	> 25 mm to ≤ 32 mm	> 32 mm to ≤ 40 mm > 40 mm	Harmonised technical
ssential characteristics/main features	Unit	Declared performance					specification	
eaction to fire		E D-s2,d0 according to EN 13986 dependent on end use (Thickness: ≥ 9 mm / Gross density: ≥ 600 kg/m³)					EN 13986:2004 +A1:2015	
ater vapour permeability, wet cup μ		15						
ater vapour permeability, dry cup μ		50						1
ass, formaldehyde release		E1 E05						
lease (Content), pentachlorophenol CP)	mg/kg	< 3						
rborne sound insulation (surface ass)		NPD						
ound Absorption frequency range 10 Hz to 500 Hz		0.1						
ound Absorption frequency range 000 Hz to 2000 Hz		0.25						
ermal conductivity (density)	W/(mK)	0.12						
r permeability		NPD						
ernal bond	N/mm²	0.4		0.35	0.3	0.25	0.2	1
elling in thickness, 24 h		NPD						
ernal bond after boil test		NPD						1

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Date of issue: 2024-04-23

i. V. Claus Seemann Head of productmanagement core materials (Document was created electronically and is therefore valid without signature!)

NPD: performance not defined Technical values refer to the core material