



## **Declaration of Performance (CE) – Ref.No 3180** acc. to REGULATION (EU) No 305/2011 Article 4 1. Identification code of ClassicBoard P3 - 3180 product-type Intended use Non load-bearing boards for use in humid conditions 3. Manufacturer Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt 4. Authorised representative not relevant System of assessment and System 4 vérification Assessment of performance not relevant European Technical not relevant



Th	Thickness		> 8.9 mm to ≤ 13 mm	> 13 mm to ≤ 20 mm	> 13 mm to ≤ 20 mm	> 20 mm to ≤ 25 mm	> 20 mm to ≤ 25 mm	> 25 mm to ≤ 32 mm	> 25 mm to ≤ 32 mm	> 32 mm to ≤ 40 mm	> 32 mm to ≤ 40 mm	larmonised technical
Essential characteristics/main features	Unit				De	clared pe	rforman	се			s	pecification
Reaction to fire											EN 3986:2004	
Water vapour permeability, wet cup µ		NPD	15	NPD	15	NPD	15	NPD	15	NPD	15	+A1:2015
Water vapour permeability, dry cup μ		NPD	50	NPD	50	NPD	50	NPD	50	NPD	50	
Class, formaldehyde release		E1 E05										
Release (Content), pentachlorophenol (PCP)	mg/kg	< 3										
Airborne sound insulation (surface mass)		NPD										
Sound Absorption frequency range 250 Hz to 500 Hz		0.1										
Sound Absorption frequency range 1000 Hz to 2000 Hz		0.25										
Thermal conductivity (density)	W/ (mK)	0.12										1
Air permeability		NPD										
Internal bond	N/ mm²	0.45				0.4		0.35		0.3		
Swelling in thickness, 24 h	%	17		14		13				12		
Internal bond after boil test		NPD										

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Date of issue: 2024-04-23

i. V. Claus Seemann Head of productmanagement core materials (Document was created electronically and is therefore valid without signature!)

NPD: performance not defined