

Declaration of Performance - Ref.No 024

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	HPL composite panel VE1520-LK																																									
2. Identification	VE1520-LK: Duropal Element MDF black																																									
3. Intended use	HPL composite panel intended for internal wall and ceiling finishes (including suspended ceilings)																																									
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D-88299 Leutkirch																																									
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D-92318 Neumarkt																																									
6. System of assessment and verification	System 4																																									
7. Assessment of performance	not relevant																																									
8. European Technical Assessment	not relevant																																									
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>VE1520-LK</th> <th rowspan="2"><i>Harmonised technical specification</i></th> </tr> <tr> <th>Thickness</th> <th>17.6–26.6 mm</th> </tr> <tr> <th><i>Essential characteristics/main features</i></th> <th><i>Declared performance</i></th> <th rowspan="16">EN 438-7:2005</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire (Euroclass)</td> <td>D-s2,d0</td> </tr> <tr> <td>Fire resistance</td> <td>NPD</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td>18</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td>27</td> </tr> <tr> <td>Resistance to fixings (face)</td> <td>min. 1,400 N</td> </tr> <tr> <td>Resistance to fixings (edge)</td> <td>min. 900 N</td> </tr> <tr> <td>Direct airborne sound insulation</td> <td>NPD</td> </tr> <tr> <td>Bonding strength</td> <td>min. 0.8 N/mm²</td> </tr> <tr> <td>Flexural tensile strength</td> <td>min. 0.8 N/mm²</td> </tr> <tr> <td>Thermal conductivity</td> <td>approx. 0.14 W/(mK)</td> </tr> <tr> <td>content of pentachlorophenol</td> <td>max. 3 ppm</td> </tr> <tr> <td>Formaldehyde release</td> <td>E1 E05 CARB Phase 2 / TSCA Title VI</td> </tr> <tr> <td>Sound absorption</td> <td>NPD</td> </tr> <tr> <td>Durability - Glue-line quality</td> <td>min. 3 rating</td> </tr> <tr> <td>Durability - Resistance to elevated temperature</td> <td>no effect</td> </tr> <tr> <td>Durability - Water resistance</td> <td>max. 20 %</td> </tr> </tbody> </table>		Identification code	VE1520-LK	<i>Harmonised technical specification</i>	Thickness	17.6–26.6 mm	<i>Essential characteristics/main features</i>	<i>Declared performance</i>	EN 438-7:2005	Reaction to fire (Euroclass)	D-s2,d0	Fire resistance	NPD	Water vapour permeability (wet cup)	18	Water vapour permeability (dry cup)	27	Resistance to fixings (face)	min. 1,400 N	Resistance to fixings (edge)	min. 900 N	Direct airborne sound insulation	NPD	Bonding strength	min. 0.8 N/mm ²	Flexural tensile strength	min. 0.8 N/mm ²	Thermal conductivity	approx. 0.14 W/(mK)	content of pentachlorophenol	max. 3 ppm	Formaldehyde release	E1 E05 CARB Phase 2 / TSCA Title VI	Sound absorption	NPD	Durability - Glue-line quality	min. 3 rating	Durability - Resistance to elevated temperature	no effect	Durability - Water resistance	max. 20 %
Identification code	VE1520-LK	<i>Harmonised technical specification</i>																																								
Thickness	17.6–26.6 mm																																									
<i>Essential characteristics/main features</i>	<i>Declared performance</i>	EN 438-7:2005																																								
Reaction to fire (Euroclass)	D-s2,d0																																									
Fire resistance	NPD																																									
Water vapour permeability (wet cup)	18																																									
Water vapour permeability (dry cup)	27																																									
Resistance to fixings (face)	min. 1,400 N																																									
Resistance to fixings (edge)	min. 900 N																																									
Direct airborne sound insulation	NPD																																									
Bonding strength	min. 0.8 N/mm ²																																									
Flexural tensile strength	min. 0.8 N/mm ²																																									
Thermal conductivity	approx. 0.14 W/(mK)																																									
content of pentachlorophenol	max. 3 ppm																																									
Formaldehyde release	E1 E05 CARB Phase 2 / TSCA Title VI																																									
Sound absorption	NPD																																									
Durability - Glue-line quality	min. 3 rating																																									
Durability - Resistance to elevated temperature	no effect																																									
Durability - Water resistance	max. 20 %																																									
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.																																										
Signed for and on behalf of the manufacturer by:																																										
Date of issue: 2021-02-02	Diethard Singer General Manager / Pfleiderer Leutkirch GmbH (Document was created electronically and is therefore valid without signature!)																																									

NPD: performance not defined