

## Declaration of Performance - Ref.No 019

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	HPL composite panel VE689-LK																																									
2. Identification	VE689-LK: Duropal Element Poplar Veneer																																									
3. Intended use	HPL composite panel intended for internal wall and ceiling finishes (including suspended ceilings)																																									
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D-88299 Leutkirch																																									
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D-92318 Neumarkt																																									
6. System of assessment and verification	System 4																																									
7. Assessment of performance	not relevant																																									
8. European Technical Assessment	not relevant																																									
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>VE689-LK</th> <th rowspan="2">Harmonised technical specification</th> </tr> <tr> <th>Thickness</th> <th>16.6–19.6 mm</th> </tr> <tr> <th><i>Essential characteristics/main features</i></th> <th><i>Declared performance</i></th> <th rowspan="16">EN 438-7:2005</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire (Euroclass)</td> <td>NPD</td> </tr> <tr> <td>Fire resistance</td> <td>NPD</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td>NPD</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td>NPD</td> </tr> <tr> <td>Resistance to fixings (face)</td> <td>min. 1,200 N</td> </tr> <tr> <td>Resistance to fixings (edge)</td> <td>min. 1,000 N</td> </tr> <tr> <td>Direct airborne sound insulation</td> <td>NPD</td> </tr> <tr> <td>Bonding strength</td> <td>min. 1.3 N/mm<sup>2</sup></td> </tr> <tr> <td>Flexural tensile strength</td> <td>min. 1.3 N/mm<sup>2</sup></td> </tr> <tr> <td>Thermal conductivity</td> <td>NPD</td> </tr> <tr> <td>content of pentachlorophenol</td> <td>approx. 3 ppm</td> </tr> <tr> <td>Formaldehyde release</td> <td>E1 E05</td> </tr> <tr> <td>Sound absorption</td> <td>NPD</td> </tr> <tr> <td>Durability - Glue-line quality</td> <td>min. 5 rating</td> </tr> <tr> <td>Durability - Resistance to elevated temperature</td> <td>no effect</td> </tr> <tr> <td>Durability - Water resistance</td> <td>max. 10 %</td> </tr> </tbody> </table>		Identification code	VE689-LK	Harmonised technical specification	Thickness	16.6–19.6 mm	<i>Essential characteristics/main features</i>	<i>Declared performance</i>	EN 438-7:2005	Reaction to fire (Euroclass)	NPD	Fire resistance	NPD	Water vapour permeability (wet cup)	NPD	Water vapour permeability (dry cup)	NPD	Resistance to fixings (face)	min. 1,200 N	Resistance to fixings (edge)	min. 1,000 N	Direct airborne sound insulation	NPD	Bonding strength	min. 1.3 N/mm <sup>2</sup>	Flexural tensile strength	min. 1.3 N/mm <sup>2</sup>	Thermal conductivity	NPD	content of pentachlorophenol	approx. 3 ppm	Formaldehyde release	E1 E05	Sound absorption	NPD	Durability - Glue-line quality	min. 5 rating	Durability - Resistance to elevated temperature	no effect	Durability - Water resistance	max. 10 %
Identification code	VE689-LK	Harmonised technical specification																																								
Thickness	16.6–19.6 mm																																									
<i>Essential characteristics/main features</i>	<i>Declared performance</i>	EN 438-7:2005																																								
Reaction to fire (Euroclass)	NPD																																									
Fire resistance	NPD																																									
Water vapour permeability (wet cup)	NPD																																									
Water vapour permeability (dry cup)	NPD																																									
Resistance to fixings (face)	min. 1,200 N																																									
Resistance to fixings (edge)	min. 1,000 N																																									
Direct airborne sound insulation	NPD																																									
Bonding strength	min. 1.3 N/mm <sup>2</sup>																																									
Flexural tensile strength	min. 1.3 N/mm <sup>2</sup>																																									
Thermal conductivity	NPD																																									
content of pentachlorophenol	approx. 3 ppm																																									
Formaldehyde release	E1 E05																																									
Sound absorption	NPD																																									
Durability - Glue-line quality	min. 5 rating																																									
Durability - Resistance to elevated temperature	no effect																																									
Durability - Water resistance	max. 10 %																																									
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.																																										

Signed for and on behalf of the manufacturer by:

Date of issue: 2021-03-02

Diethard Singer  
General Manager / Pfleiderer Leutkirch GmbH  
(Document was created electronically and is therefore valid without signature!)

NPD: performance not defined