

Declaration of Performance - Ref.No 051

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	High-pressure decorative compact laminate CGS-AR High-pressure decorative compact Laminate with design effect ACS-AR																																																																																																					
2. Identification	CGS-AR: Duropal HPL Compact, black core ACS-AR: Duropal HPL Compact Metallic, black core																																																																																																					
3. Intended use	Compact laminate intended for internal wall and ceiling finishes (including suspended ceilings)																																																																																																					
4. Manufacturer	Pfleiderer Arnsberg GmbH, Westring 19-21, D-59759 Arnsberg																																																																																																					
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D-92318 Neumarkt																																																																																																					
6. System of assessment and verification	System 4																																																																																																					
7. Assessment of performance	not relevant																																																																																																					
8. European Technical Assessment	not relevant																																																																																																					
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>CGS-AR ACS-AR</th> <th>CGS-AR ACS-AR</th> <th>CGS-AR ACS-AR</th> <th>CGS-AR ACS-AR</th> <th>CGS-AR ACS-AR</th> </tr> </thead> <tbody> <tr> <td>Thickness</td> <td>2-3 mm</td> <td>4-5 mm</td> <td>6-7 mm</td> <td>8-9 mm</td> <td>10-15 mm</td> </tr> <tr> <td><i>Essential characteristics/main features</i></td> <td colspan="5"><i>Declared performance</i></td> </tr> <tr> <td>Reaction to fire (Euroclass)</td> <td colspan="2">NPD</td> <td colspan="3">D-s2,d0</td> </tr> <tr> <td>Fire resistance</td> <td colspan="5">NPD</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td colspan="5">110</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td colspan="5">250</td> </tr> <tr> <td>Resistance to fixings (face)</td> <td>min. 250 N</td> <td>min. 1,000 N</td> <td>min. 2,000 N</td> <td>min. 3,000 N</td> <td>min. 4,000 N</td> </tr> <tr> <td>Resistance to fixings (edge)</td> <td colspan="5">NPD</td> </tr> <tr> <td>Direct airborne sound insulation</td> <td colspan="5">NPD</td> </tr> <tr> <td>Flexural tensile strength</td> <td colspan="5">passed</td> </tr> <tr> <td>Thermal conductivity</td> <td colspan="5">approx. 0.3 W/(mK)</td> </tr> <tr> <td>Formaldehyde release</td> <td colspan="5">E1</td> </tr> <tr> <td>Sound absorption</td> <td colspan="5">NPD</td> </tr> <tr> <td>Durability - Resistance to immersion in boiling water</td> <td colspan="5">passed</td> </tr> <tr> <td>Density</td> <td colspan="5">min. 1,350 kg/m³</td> </tr> </tbody> </table>					Identification code	CGS-AR ACS-AR	CGS-AR ACS-AR	CGS-AR ACS-AR	CGS-AR ACS-AR	CGS-AR ACS-AR	Thickness	2-3 mm	4-5 mm	6-7 mm	8-9 mm	10-15 mm	<i>Essential characteristics/main features</i>	<i>Declared performance</i>					Reaction to fire (Euroclass)	NPD		D-s2,d0			Fire resistance	NPD					Water vapour permeability (wet cup)	110					Water vapour permeability (dry cup)	250					Resistance to fixings (face)	min. 250 N	min. 1,000 N	min. 2,000 N	min. 3,000 N	min. 4,000 N	Resistance to fixings (edge)	NPD					Direct airborne sound insulation	NPD					Flexural tensile strength	passed					Thermal conductivity	approx. 0.3 W/(mK)					Formaldehyde release	E1					Sound absorption	NPD					Durability - Resistance to immersion in boiling water	passed					Density	min. 1,350 kg/m ³					<i>Harmonised technical specification</i>
Identification code	CGS-AR ACS-AR	CGS-AR ACS-AR	CGS-AR ACS-AR	CGS-AR ACS-AR	CGS-AR ACS-AR																																																																																																	
Thickness	2-3 mm	4-5 mm	6-7 mm	8-9 mm	10-15 mm																																																																																																	
<i>Essential characteristics/main features</i>	<i>Declared performance</i>																																																																																																					
Reaction to fire (Euroclass)	NPD		D-s2,d0																																																																																																			
Fire resistance	NPD																																																																																																					
Water vapour permeability (wet cup)	110																																																																																																					
Water vapour permeability (dry cup)	250																																																																																																					
Resistance to fixings (face)	min. 250 N	min. 1,000 N	min. 2,000 N	min. 3,000 N	min. 4,000 N																																																																																																	
Resistance to fixings (edge)	NPD																																																																																																					
Direct airborne sound insulation	NPD																																																																																																					
Flexural tensile strength	passed																																																																																																					
Thermal conductivity	approx. 0.3 W/(mK)																																																																																																					
Formaldehyde release	E1																																																																																																					
Sound absorption	NPD																																																																																																					
Durability - Resistance to immersion in boiling water	passed																																																																																																					
Density	min. 1,350 kg/m ³																																																																																																					
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.																																																																																																						

Signed for and on behalf of the manufacturer by:

Date of issue: 2020-01-16

Erwin Sversepa
General Manager / Pfleiderer Arnsberg GmbH
(Document was created electronically and is therefore valid without signature!)

NPD: performance not defined